

ADVANCED TECHNOLOGY - WATER BASED

PLATINUM ACQUA



DESCRIPTION: ANTI STAIN WATER BASED IMPREGNATOR TREATMENT

RECOMMENDED USE: POLISHED AND HONED MATT TEXTURED FINISH GRANITE, MARBLE, NATURAL AND ARTIFICIAL ENGINEERED STONES, TERRA COTTA, QUARRY, CEMENT PAVERS.

- Natural finish for interior and exterior use
- Effective for honed and polished natural stones - Flooring –Work surfaces (Kitchen, Bathrooms)
- Odourless
- Non Toxic Environmentally friendly

PLATINUM ACQUA IS “FOOD CONTACT CERTIFICATED”



PROPERTIES:

PLATINUM ACQUA penetrates the surface of the stone creating an invisible barrier protection against stains: - Oil, Grease, Coffee, Tea, Food, General Dirt, Mould and Mildew.

Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching, we recommend any spillage be cleaned up as a matter of good housekeeping.

APPLICATION:

All stone surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone. Where necessary ensure all surrounding areas and surfaces sensitive to solvents are protected against any spillage.

Apply one coat of PLATINUM ACQUA evenly by spraying using a low pressure pump up garden spray type unit (most efficient method) or with a lamb's wool applicator or by cloth in circular movements and allow to dry for approx. 6-8hours. On very absorbent surfaces two or third coats may be required allowing sufficient time between each additional application (20-30 minutes) to penetrate into the stone and dry. If in doubt test discreet area to ensure second or third application is necessary.

In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper.

Temperature of surface to be treated should not be below 10°C.

Avoid direct sunlight especially for external works.

Drying time: Dry 2 to 3 hours, safe to walk on carefully .

Fully effective within 48-72 hours before resuming normal use.

Important Safety Note

When using any type of product suitable ventilation should be provided during and after application .Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on Material Safety Data Sheet.

STORE: Dry surroundings above + 0°C

COVERAGE:

Indicative usage based on 2 coats, and subject to stone absorption and surface texture.

- High Porosity Stone, Sandstone 5- 6m²
- Medium Porosity, Honed Stone, Limestone 8– 12m²
- Low Porosity Stone 15 – 25m²
- Very Dense Stone 30 – 40m²

RECOMMENDATION:

Flooring and work tops routine cleaning antibacterial STONE CLEAN . Intensive or periodic clean where additional effort is required we recommend using MASTER CLEAN detergent.

Packaging:

10 x 1 LT

2 x 5 LT

All childproof tamper evident cap



Food Contact Certified