

PLATINUM BLACK



TOTALIZING PIGMENTED IMPREGNATING AGENT

DESCRIPTION



Solvent-based formulation for the darkening treatment of granites, black stone materials and cement agglomerates. PLATINUM BLACK totally eliminates the natural stains present in the conformation of the support and thanks to the impregnated action, which allows a perfect saturation of the micro pores by eliminating the shading, it allows to obtain a uniform surface in the color.

Our product not only has excellent durability over time, thanks to its resistance to UVA rays, it also allows a greater cleanability of the surface thanks to the protective water-repellent action, it colors without leaving surface films.

PLATINUM BLACK can be applied on any type of stone material and on agglomerates with finishing: glossy, flamed, brushed, sandblasted, smoothed, rough. PLATINUM BLACK can be applied both on slabs to be stored in the warehouse and on finished products, before or after installation; it can also be used for maintenance or restoration of surfaces with the presence of white halos from abrasion, aggression of acidic substances, halos caused by acid rains.

YIELD

The yield varies from 4 to 30 m² of surface with 1 L of product.

- Glossy surfaces: 25-30 m²/L
- Brushed surfaces: 20-25 m²/L
- Polished surfaces: 15-20 m²/L
- Rough surfaces: 4-6 m²/L

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product. Do not eat or drink when using this product.

APPLICATION

Apply PLATINUM BLACK on well cleaned and dry surfaces.

· *For the treatment of slabs*, apply one or more coats of product depending on the absorbency of the stone material or the type of tone you want to obtain, taking care to spread it evenly with a brush, roller or cotton cloth; a second coat must be applied, not earlier than 12/24 hours after removal of the surplus, at complete drying or rather after 24/36 hours with the use of manual brushes or directly in line with the polishing heads.

· *For the treatment of the finished products*, pour PLATINUM BLACK directly on the surfaces and spread it evenly with brush, cotton cloth or spray, let it dry for at least 3-4 hours then remove the surplus.

· *For surfaces in agglomerated cement and grit*, remove the surplus immediately after the application of the product.

RECOMMENDATIONS

For routine cleaning of surfaces treated with PLATINUM BLACK avoid the use of acid-based products. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.