

REFLECT WAX

SOLVENT-BASED ODOURLESS PASTE WAX



DESCRIPTION

Paste-looking wax suitable for polishing and protecting marble and granite surfaces, agglomerate, natural stone. The components present in the wax provide the treated surfaces an excellent shine together with a long lasting, thanks to the strong penetration power and the remarkable resistance. Thanks to these properties it is possible to eliminate defects due to small cracks or loss of shine, achieving a gloss without halos.

REFLECT WAX is also an excellent repellent and anti-dirt. Not only it is used for stone materials but it is also widely used in the treatment of patination of the Venetian stucco and spatulated in lime.

YIELD

The yield varies from 10 to 50 m² of surface with 1 L of product

APPLICATION

Apply small quantities of REFLECT WAX on the surface to be treated with circular movements using a cotton cloth, making it penetrate into the stone material. After waiting 30/60 minutes, pass by hand with a cotton cloth or a wool of fine iron or bristle brush, until you obtain the desired gloss. For floors, spread REFLECT WAX with a monobrush equipped with an anti-scratch white pad.

After drying, refine with a soft felt.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

Avoid the application of REFLECT WAX on floors or surfaces with heating systems in contact (heating underfloor). The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C.

Always protect yourself with mask, gloves and protective clothing. Any surplus can be removed with SOLVENT STRIPPER.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.