

SEAL & TONE

**SOLVENT-BASED, WATER-OIL REPELLENT, ANTI-STAIN
PROTECTIVE WITH WET EFFECT**



YIELD

**The yield varies from 6 to
30 m² of surface with 1 L of
product.**

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

DESCRIPTION

Product designed for an anti-stain protection with a reviving (and toning) effect of stone materials with brushed or glossy finish, tumbled, disc cutting, etc.

It's suitable for the treatment of marble, granite, gneiss, slate, sandstone, lava stone, limestone, agglomerates of cement, quartzite, diorite. SEAL & TONE penetrates into the material, protecting it from staining substances in general, trampling dirt, smog and atmospheric dirt, highlighting the natural colors of the treated surface. It does not form surface films.

SEAL & TONE is particularly suitable for antiqued marbles and strong colored stones, it is suitable for interior surfaces and it is compatible with self-polishing finishing products, such as SURFACE.

The product is resistant to routine washing carried out with appropriate detergents such as STONE CLEAN and MASTER CLEAN, used manually or with floor cleaning machines.

APPLICATION

SEAL & TONE can be applied, on clean and dry surfaces, by roller, brush, spray or cotton cloth. Apply one or two times depending on the surface to protect.

Regardless of the method of application, remove any surplus product by using a cotton or microfiber cloth. When the product is dry, wipe with a clean, dry cloth to give more coating to the treated surface.

Below there is the indicative yield depending on the type of processing:

- Polished 10/20 m²/L
- Tumbled 10/15 m²/L
- Flamed 6/8 m²/L
- Brushed 25/30 m²/L
- Bush-hammered 6/8 m²/L
- Disc cutting 6/8 m²/L
- Sandblasted 6/8 m²/L

RECOMMENDATIONS

For routine maintenance, use the neutral detergent STONE CLEAN.

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10°C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.