

WATEREP – AQ

WATER BASED DIRT / WATER REPELLENT TREATMENT



DESCRIPTION

WATEREP-AQ penetrates the surface of the stone creating an invisible barrier protection against stains caused by general dirt, mould and mildew. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant.

- Suitable for concrete, granite, cement, terra cotta and plaster.
- Suitable for facade, pillar and balcony.
- Effective treatment for exterior surfaces in constant contact with water , weathering.
- Effective water repellent action against general water, dirt, smog mould, mildew stains.
- Lasts 5 years.



APPLICATION

All stone surfaces to be treated must be completely clean and dry.
Apply WATEREP – AQ with brush, roller or by spraying using a low pressure pump.
On very absorbent surfaces apply a second coat before the previous one is dry.

ADVICE

Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product.
Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

COVERAGE

SANDBLASTED SURFACES: 3-5 m²/L
CONCRETE: 4-8 m²/L
POLISHED SURFACES: 6-8 m²/L

PACKAGING

10 x 1 l bottle
2 x 5 l tank
1 x 25 l tank
1 x 60 l tank
All childproof tamper evident cap

Other packaging available on request

BEFORE USING PRODUCT TEST SMALL AREA

Use appropriate personal protection equipment, gloves, safety glasses and clothing as appropriate. Before proceeding, to avoid damages from accidental spills or vapours, remove or protect all objects with appropriate protection and tape .Protect as necessary all surrounding areas, glass, metal, aluminium or plants and allow appropriate ventilation. Keep product well closed and out of reach of children.

Detailed information are reported in the Material Safety Data Sheets compliant with Regulation (CE) 1272/2008 (CPL) and with Regulation (UE) 2015/830.

