ACCADUEO



WATER-BASED NEUTRAL WATER-OIL REPELLENT ANTI-STAIN PROTECTIVE



YIELD

The yield varies from 10 to 40 m² of surface with 1 L of product for 2 coats.

- · MATT POLISHED: 10-15 m²/L
- · BRUSHED: 20-30 m²/L
- · GLOSSY: 30-40 m²/L
- * Product certificated for safe food contact

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

DESCRIPTION

ACCADUEO is a water-based anti-stain product suitable for protection and consolidation of stone surfaces. Its formulation is the result of years of experience in the sector of treatment of stone surfaces. In addition to maintaining the protection characteristics of solvent-based products, this product, thanks to its compatibility with water, allows you to significantly reduce intervention times and related costs, just think of the downtime caused by waiting for the drying of surfaces after washing, before treatment. Despite its total compatibility with water, it is recommended not to apply it on wet supports that, while not nullifying the effectiveness of the treatment, they would make it less valid as it is held over time, the product does not alter the degree of slipperiness of the support. It is possible to overlap ACCADUEO with finishing products, waxes or water-based resins without any problems. The product is applied on: marble, granite, gneiss, volcanic stones, basalts, agglomerates and in general all the supports that have poor absorption, it can be used for flooring, cladding, facades, ventilated walls, etc. Recommended for cement agglomerates and finishing grit glossy.

APPLICATION

ACCADUEO can be applied by brush, spray, roller, cloth, up to saturation of the support, or in two hands crossed at a distance at least three hours between them. We indicate below, based on our experience, the types of application to be carried out on a series of finishes:

- · GLOSSY SURFACES with cloth
- · BRUSHED with cloth
- · POLISHED with cloth

RECOMMENDATIONS

ACCADUEO diluted in water can be used periodically (6/12 months) to restore the effectiveness of the treatment. The product cannot stand freezing, store it in well-closed and wellprotected places, at a temperature not lower than 10 °C. Always protect yourself with suitable means of personal protection, especially for eyes and hands.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.