

## BASIC SOLUTION FOR THE REMOVAL OF SMOG, CARBON RESIDUES, BLACKENING



### DESCRIPTION

DESMOG is a basic solution, with a slightly dense consistency, formulated for effective cleaning of external facades in marble, granite, gneiss, sandstone, volcanic stones, lava stones, limestone, both glossy and rough, in bricks, cement, cement agglomerates and grit. Our product allows easy and effective cleaning of dirt caused by smog, carbon residues, atmospheric dirt, etc. DESMOG shows monuments and cladding surfaces such as facades, pillars, barriers, to their original appearance, without damaging them in any way.

### APPLICATION

After wetting the surface to be cleaned with water, apply DESMOG by brush or roller; leave it to act for about 10 minutes making sure not to let the product dry.

To obtain a more effective result, it is recommended to review the wet brush of DESMOG again after a few minutes, performing friction movements. Rinse immediately with a strong jet of water. If further traces of dirt are visible, a new wash will remove the last residues. The use of water to pressure allows a thorough cleaning even in the most deep porosities.

### YIELD

**The yield varies from 2 to 10 m<sup>2</sup> of surface with 1 kg of product.**

- Glossy/polished surfaces: 8-10 m<sup>2</sup>/kg
- Rough surfaces: 3-5 m<sup>2</sup>/kg
- Grits, cements, terracotta: 2-4 m<sup>2</sup>/kg

### ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

### RECOMMENDATIONS

Avoid contact with elements such as aluminium, copper, etc. Always have suitable means of personal protection, especially for eyes and hands. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C.

### NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.