

# GRAFFITI P

## SOLVENT-BASED ANTI-WRITING PROTECTION FOR ROUGH SURFACES



### DESCRIPTION

GRAFFITI P is a solvent-based product suitable for protection against writing and soiling caused by spray paints, markers of rough surfaces in marble, granite, stone natural, agglomerates of cement and plaster. The product forms an invisible barrier suitable to prevent the absorption of soiling agents, significantly limiting their penetration into the support.

GRAFFITI P allows to intervene for the removal of such stains using cleaning products and equipment for common use. The product can be completely removed if necessary by the use of a suitable solvent.

GRAFFITI P allows the cleaning of the support even with the only use of pressurized water using the water cleaner with minimum 150 atmospheres.

In the case of very resistant paints, complete the cleaning by the use of specific solvents.

### YIELD

**The yield varies from 4 to 15 m<sup>2</sup> of surface with 1 L of product.**

- Very absorbent surfaces: 4-6 m<sup>2</sup>/L
- Low absorbent surfaces: 10-15 m<sup>2</sup>/L

### APPLICATION

GRAFFITI P can be applied uniformly by brush or spray. In the case of highly absorbent surfaces, a second hand after 6-12 hours is recommended. The treatment becomes effective after about 36-48 hours; do not apply with temperatures below 10 °C or on excessively wet substrates, the product is ready to use.

### ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

### RECOMMENDATIONS

If solvents are used to remove writings, provide the application of an additional coat of product in order to regenerate the treatment on the surface. Always have suitable means of personal protection, especially for the eyes and hands. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C.

### NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.