

STONE PROTECTION- WATER BASED

GRAFFITI - W



DESCRIPTION: ANTIGRAFFITI WATER BASED PAINT / GRAFFITI REPELLENT TREATMENT FOR POLISHED AND NATURAL STONE SURFACES

RECOMMENDED USE: SUITABLE FOR ALL GRANITE, MARBLE, NATURAL STONES (LIMESTONE, SANDSTONE) AND CEMENT BASED SURFACES.

- Effective for interior and exterior use
- Effective protection against paint, graffiti and felt pen marks.
- Highly recommended for exterior facades and monuments and head stone surroundings.
- Effective water and dirt repellent properties.
- Effective application on slightly damp surfaces
- Eco friendly



PROPERTIES: **GRAFFITI -W** penetrates deep inside the stone creating an invisible barrier against graffiti attacks and due unique formulation is water and dirt repellent. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant.

Important Safety Note: When using any type of solvent based product suitable ventilation should be provided during and after application .Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on the MSDS SHEET (Material Safety Data Sheet).

Application:

All stone surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone. Where necessary ensure all surrounding areas and surfaces sensitive to solvents are protected against any spillage.

Apply one coat of **GRAFFITI - W** evenly by spraying using a low pressure pump up garden spray type unit or with a clean brush uniformly. The most efficient method is by spraying.

On very absorbent surfaces apply a second coat allowing sufficient time approximately 6 – 12 hours for your first application to penetrate into the stone and dry. If in doubt test discreet area to ensure second application is necessary.

In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper.

Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

Drying time: - Fully effective within 24 -48 hours before resuming normal use.

STORE:

Dry surroundings above + 0°C

COVERAGE PER LT:

Indicative coverage subject to stone absorption, surface texture.

High Porosity Stone: 3 – 6m²

Medium-Low Porosity Stone. 6 – 10m²

***Coverage:** The information is purely a guide line only and may differ according to the porosity and textured finish of the stone and site conditions.

RECOMMENDATION:

Cleaning off graffiti marks on surfaces already treated with **GRAFFITI -W** can be carried out using water jet to remove any heavy duty graffiti and or combination with our "MASTER CLEAN" alkaline detergent diluted and nylon type scouring pad as final wash.

It is always recommended to re treat stone surfaces after several washes to re in force premium protection.

Packaging:

10 x 1 litre

2 x 5 litre container

All childproof tamper evident cap