

RUST CLEAN

ACID PRODUCT FOR THE REMOVAL OF RUST FROM NATURAL STONES



YIELD

The yield varies from 1 to 10 m² of surface with 1 kg of product.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

DESCRIPTION

Specific product for the removal of rust and oxidation from natural stones in general.

RUST CLEAN provides an effective action on any type of surface and specifically on materials such as beole, quartzites, serizzo and all those stone materials that have ferrous minerals in their composition which, in contact with constant humidity or water present in the laying mixes, tend to oxidize giving rise to yellowish halos.

RUST CLEAN can be applied both indoors and outdoors and on laid surfaces rather than on machined to be laid. It is recommended to the marble workers to eliminate the residues of filing after cutting or for the removal of oxidations due to contact with metal materials.

APPLICATION

DO NOT APPLY ON ANY KIND OF GLOSSY OR BRUSHED MARBLES.

It is applicable on any other glossy material that does not contain calcite such as: gneiss, serizzo, granite, volcanic stone, porphyry, quartzite and diorite.

It can be applied pure or diluted in water depending on the type of oxidation to be removed, taking care to wet with water the part to be rusted before applying the product. Leave it to act for at least 30 minutes and rinse with plenty of water. In some cases it needs to act even for a few hours.

The product should not dry on the surface to avoid that the absorption could give rise to dark halos; after the rust removal treatment is recommended a neutralizing wash with PROCLEAN 04 diluted in 10% water.

Dilution

- Light cleaning - Dilute 1 part of RUST CLEAN with 2 parts of water. (1:2)
- Concentrated cleaning - Dilute 1 part of RUST CLEAN with 1 part of water. (1:1)
- For a stronger and faster action apply pure RUST CLEAN.

RECOMMENDATIONS

In case of use in situations where there are metal objects based on aluminum, copper and brass, it is advisable to protect them to avoid oxidation or the formation of dark stains.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.