

SOLVENT STRIPPER

SOLVENT-BASED WAX REMOVER WITH SLOW EVAPORATION



YIELD

The yield varies from 1 to 15 m² of surface with 1 L of product.

DESCRIPTION

SOLVENT STRIPPER is composed of a mixture of slow evaporating solvents for the removal of excess protective anti-stain treatments made both on glossy and rough stone materials and on terracotta surfaces. The product acts effectively on excess treatment due to incorrect applications, without altering the surface. SOLVENT STRIPPER does not affect the gloss, evens the surfaces and does not leave halos. Our product is an excellent wax remover for terracotta surfaces and can be used manually or with floor-washing machines. SOLVENT STRIPPER completely removes glue residues from adhesive tape or posters, lightweight inks and silicone residues. The product can be used for deep cleaning before carrying out a protective treatment eliminating downtime caused by waiting for the drying of the supports in the case of cleaning with water-based detergents. SOLVENT STRIPPER is ideal for removal of the stratification of old waxes from floors in terracotta of old laying and recovery. SOLVENT STRIPPER is a ready-to-use product.

APPLICATION

SOLVENT STRIPPER can be applied by hand with a cloth or by spray.

Leave it act a few minutes and then rub with a cloth or with a monobrush equipped with a disc in Tynex and Scotch-Brite black/green and then vacuum with a wet vacuum cleaner.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

Avoid contact with elements in fiberglass, plexiglass, polycarbonate and parquet.

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.