

SOLVENT-BASED NEUTRAL WATER-REPELLENT



DESCRIPTION

Water repellent anti-saltpetre suitable for the protection of facades, prefabricated panels and natural stone exterior cladding, reconstructed stones, exposed concrete, cement and lime various type, terracotta. The product is a solution of siloxane resins in solution solvent that after drying leave the support neutral and without superficial films, breathable and non-yellowing. WATER REP prevents the absorption of rainwater and a significant decrease in penetration dust, atmospheric dirt, organic substances, molds, allowing to keep the surfaces well clean during the years, and to avoid the degradation caused by the absorption of acid rain; it has good resistance to U.V. rays. Our facade product has a life of at least five years, but there are cases where after 20 years WATER REP continues to maintain its effectiveness.

YIELD

The yield varies from 3 to 6 m² of surface with 1 L of product.

- Smooth surfaces of 6 m²/L
- Rough surfaces of 3-4 m²/L
- Concrete agglomerate of 4-5 m²/L

APPLICATION

The product can be applied by brush, roller, spray with a pump at low pressure, on well cleaned and dry surfaces, in a passage abounding and in the case of very absorbent supports with a second hand before the previous one is dry.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

In case of application on coverings with the presence of wooden windows, we recommend to protect them to avoid contact with the product. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing. Application on horizontal surfaces is not recommended.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.